

[CLICK HERE FOR FULL CATALOGUE](#)

Model name	FTKS40EVR	FTKS40EVR	FTKS50EVR	FTKS71EVR	FTKS80EVR
Supply	1 phase, 220-240 V, 50 Hz		1 phase, 230 V, 50 Hz		
Colour	Ivory white				
Compressor type	Hermetically sealed swing type				
Sound levels	dB (A)	47/43*1	46/43*1	48/45*1	
Dimensions (H x W x D)	mm	550 x 765 (+75*2) x 285	735 x 826 (+110*2) x 300		770 x 900 x 320
Net weight	kg	38	49	58	69
Operating range	°CDB	10 to 46			
Coil length	m	30 (total) 20 (for each room)	50 (total)	60 (total) 25 (for each room)	70 (total)
Cost of additional charge	€/m	20 (for 20 m or more)*3		Chargeless	
Installation reference	* To be used between indoor and outdoor units				

**Wall-mounted type**

Model name	FTKS25DVM	FTKS35DVM	FTKS50DVM	FTKS60DVM	FTKS71DVM	
Supply	1 phase, 220-240 V, 50 Hz/1 phase, 220-230 V, 60 Hz		1 phase, 220-240 V, 50 Hz/1 phase, 220-230 V, 60 Hz			
Panel colour	White					
Flow rates (H)	m <sup>3</sup> /min (cfm)	8.7 (307)	8.9 (314)	14.7 (519)	16.2 (572)	17.4 (614)
Sound levels (H/L/SL)	dB (A)	37/25/22	39/26/23	43/34/31	45/36/33	46/37/34
Control speed	5 steps, quiet and automatic					
Temperature control	Microcomputer control					
Dimensions (H x W x D)	mm	283 x 800 x 195		290 x 1,050 x 238		
Piping connections	mm	ø9.5		ø6.4 ø18.0	ø12.7	ø15.9
Heat insulation	Both liquid and gas pipes					

Power :  
Casing  
Compre  
Sound  
Dimens  
Machin  
Operati  
Max. pi  
Necess  
Max. ir  
Wal  
Mach  
Pow  
Front  
Airflow  
Sour  
Fan :  
Tem  
Dime  
Mach