

[CLICK HERE FOR FULL CATALOGUE](#)

Model name	2MKS40FV1B		3MKS50ESG		3MKS71ESG		4MKS80ESG	
Power supply	1 phase, 220-240 V, 50 Hz		1 phase, 230 V, 50 Hz					
Casing colour	Ivory white							
Compressor type	Hermetically sealed swing type							
Sound levels	dB (A)	47/43*1		46/43*1		48/45*1		
Dimensions (H x W x D)	mm	550 x 365 x 752 (+385 x 200)		735 x 826 (+110*2) x 300			770 x 900	
Machine weight	kg	38		49		58		69
Operation range	*CDB			10 to 46				
Max. piping length	m	30 (total)		50 (total)		60 (total)		70 (total)
Necessity of additional charge	g/m	20 (for 20 m or more)*3				25 (for 20 m or more)		
Max. installation height difference	m			15 (between indoor and outdoor units)		Chargeless		

#### Wall-mounted type

71FVM	Model name		FTKS25DVM		FTKS35DVM		FTKS50FVM		FTKS60FVM		FTKS71FVM		
Hz	Power supply		1 phase, 220-240 V, 50 Hz		1 phase, 220-230 V, 60 Hz		1 phase, 220-240 V, 50 Hz		1 phase, 220-230 V, 60 Hz		1 phase, 220-240 V, 50 Hz		
	Front panel colour		White		White		White		White		White		
(614)	Airflow rates (H)	m <sup>3</sup> /min (cfm)	8.7 (307)		8.9 (314)		14.7 (519)		16.2 (572)		17.4 (614)		
(37/34)	Sound levels (H/L/S/L)	dB (A)	33/25/22		33/26/23		43/34/31		45/36/33		46/37/34		
	Control		Microcomputer control		Microcomputer control		Microcomputer control		Microcomputer control		Microcomputer control		
	Temperature control		Microcomputer control		Microcomputer control		Microcomputer control		Microcomputer control		Microcomputer control		
	Dimensions (H x W x D)	mm	283 x 800 x 195		283 x 800 x 195		290 x 1,050 x 238		290 x 1,050 x 238		290 x 1,050 x 238		
	Machine weight	kg	9		9		12		12		12		
	Piping connections	Liquid (flare)	mm	ø9.5		ø6.4		ø6.4		ø12.7		ø12.7	
		Gas (flare)		ø9.5		ø6.4		ø12.7		ø12.7			
		Drain		ø9.5		ø6.4		ø12.7		ø12.7			
ø15.9	Refrigerant		R410A		R410A		R410A		R410A		R410A		
	Installation		Both liquid and gas pipes		Both liquid and gas pipes		Both liquid and gas pipes		Both liquid and gas pipes		Both liquid and gas pipes		