

[CLICK HERE FOR FULL CATALOGUE](#)

Model name	2MKS40FV1B	3MKS50ESG	3MKS71ESG	4MKS80ESG
Power supply	1 phase, 220-240 V, 50 Hz	1 phase, 220-240 V, 50 Hz	1 phase, 220 V, 50 Hz	1 phase, 220 V, 50 Hz
Casing colour			Ivory white	
Compressor type			Hermetically sealed	swing type
Sound levels	dB (A)	47/43*1	46/43*1	48/45*1
Dimensions (H x W x D)	mm	550 x 765 (+75*2) x 285	735 x 826 (+110*2) x 300	
Machine weight	kg	38	49	58
Operation range	CDB		10 to 46	
Max. piping length	m	30 (total)	50 (total)	60 (total)
Necessity of additional charge	g/m	20 (for each room)	25 (for each room)	30 (for each room)
Max. installation height difference	m	20 (for 20 m or more)	15 (between indoor and outdoor units)	

Wall-mounted type

Model name	FTKS25DVM	FTKS35DVM	FTKS50FVM	FTKS60FVM	FTKS71FVM
Power supply	1 phase, 220-240 V, 50 Hz	1 phase, 220-230 V, 60 Hz	1 phase, 220-240 V, 50 Hz	1 phase, 220-230 V, 50 Hz	1 phase, 220-230 V, 50 Hz
Front panel colour			White		
Airflow rates (H)	m ³ /min (cfm)	8.7/30.7	11.1/39.4	13.8/47.3	16.5/56.7
Sound levels (H/L/SL)	dB (A)	37/25/22	39/26/23	43/31/28	45/33/30
Fan speed			5 steps, quiet and automatic		
Temperature control	microcomputer control		Microcomputer control	Microcomputer control	Microcomputer control
Dimensions (H x W x D)	mm	283 x 800 x 95	290 x 1,050 x 238		