

[CLICK HERE FOR FULL CATALOGUE](#)

Model name	2MKS40FV1B	3MKS50ESG	3MKS71ESG	4MKS80ESG
Power supply	1 phase, 220-240 V, 50 Hz		1 phase, 230 V, 50 Hz	
Casing colour	Ivory white			
Compressor type	Hermetically sealed swing type			
Sound levels	dB (A) 47/43*1	46/43*1		48/45*1
Dimensions (H x W x D)	mm 550 x 765 (+75*2) x 285	735 x 826 (+110*2) x 300		770 x 900 x 320
Machine weight	kg 38	49	58	69
Operation range	°CDB 10 to 46			
Max. piping length	m 30 (total) 20 (for each room)	50 (total)	60 (total) 25 (for each room)	70 (total)
Necessity of additional charge	g/m 20 (for 20 m or more)*3	Chargeless		
Max. installation height difference	m 15 (between indoor and outdoor units)			

Wall-mounted type

Model name	FTKS25DVM	FTKS35DVM	FTKS50FVM	FTKS60FVM	FTKS71FVM
Power supply	1 phase, 220-240 V, 50 Hz	1 phase, 220-230 V, 60 Hz	1 phase, 220-240 V, 50 Hz/1 phase, 220-230 V, 60 Hz		
Front panel colour	White				
Airflow rates (H)	m ³ /min (cfm) 8.7 (307)	8.9 (314)	14.7 (519)	16.2 (572)	17.4 (614)
Sound levels (H/L/SL)	dB (A) 37/25/22	39/26/23	43/34/31	45/36/33	46/37/34
Fan speed	5 steps, quiet and automatic				
Temperature control	Microcomputer control				
Dimensions (H x W x D)	mm 283 x 800 x 195		290 x 1,050 x 238		
Machine weight	kg 9		12		
Piping connections	Liquid (flare)		ø6.4		
	Gas (flare)	mm ø9.5	ø12.7		ø15.9
	Drain		ø18.0		
Heat insulation	Both liquid and gas pipes				