

[CLICK HERE FOR FULL CATALOGUE](#)

Model name		2MKS40FV1B	3MKS50ESG	3MKS71ESG	4MKS80ESG
Power supply		1 phase, 220-240 V, 50 Hz		1 phase, 230 V, 50 Hz	
Casing colour		Ivory white			
Compressor type		Hermetically sealed swing type			
Sound levels	dB (A)	47/43*1	46/43*1		48/45*1
Dimensions (H x W x D)	mm	550 x 765 (+75*2) x 285	735 x 826 (+110*2) x 300		770 x 900 x 320
Machine weight	kg	38	49	58	69
Operation range	°CDB	10 to 46			
Max. piping length	m	30 (total)	50 (total)	60 (total)	70 (total)
		20 (for each room)		25 (for each room)	
Necessity of additional charge	g/m	20 (for 20 m or more)*3		Chargeless	
Max. installation height difference	m	15 (between indoor and outdoor units)			

### Wall-mounted type

Model name		FTKS25DVM	FTKS35DVM	FTKS50FVM	FTKS60FVM	FTKS71FVM
Power supply		1 phase, 220-240 V, 50 Hz	1 phase, 220-230 V, 60 Hz	1 phase, 220-240 V, 50 Hz/1 phase, 220-230 V, 60 Hz		
Front panel colour		White				
Airflow rates (H)	m <sup>3</sup> /min (cfm)	8.7 (307)	8.9 (314)	14.7 (519)	16.2 (572)	17.4 (614)
Sound levels (H/L/SL)	dB (A)	37/25/22	39/26/23	43/34/31	45/36/33	46/37/34
Fan speed		5 steps, quiet and automatic				
Temperature control		Microcomputer control				
Dimensions (H x W x D)	mm	283 x 800 x 195			290 x 1,050 x 238	
Machine weight	kg	9			12	
Piping connections	Liquid (flare)	ø9.5			ø6.4	
	Gas (flare)	ø9.5			ø12.7	
	Drain	ø9.5			ø18.0	
Heat insulation		Both liquid and gas pipes				