## CLICK HERE FOR FULL CATALOGUE

Outdoor unit	Combinations of indoor units	Capacity of each indoor unit (kW)	Total capacity (kW)	Total power consumption (W	Total running current (A)	Power factor (%)			
5.8±53 - T	92	: 음 6클 - 25:	s <u>_ 12</u> , 90	= 2.67	> ≝를 2.0	57.5 - 1170			
6.0	3 92 35 3.40 3.40 1210								
61	92	- 25+2	5	1,98+1.98	3.9	1225			
	20+30	5 05 1.70+2:55 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	54.25	1235	16:1	≗ i 92.			
IA45EV1	35+35	2.24+2.24	4.48	1240 -	6.1	92. N			
92	05-05 05 -Z	2+25+25 - 49+1.	49+1.49	4.47	1240 -	6. <u>1</u> 11			
92	25	5+25+35 1.31+1.	31+1.97	4.59	1240	6.1			
.00	32	1136136 EUTUUTUU 16:14	76:1-29-11:00-11	10+1:46%	19480				

ning Power fa	Power factor (%)		Combinations	Capacity of each		Total capacity	Total power	Total rur						
6.9 9		98	25		2.56		2.56	1490						
7.0	Constant State	98		35	3 66		3.66	1500						
	- <sup>-</sup> 25	720	^2 <del>5</del> 5 <del>3</del> 255	4.30	1520	<i>₹</i> .0	<u> </u>	99 9						
	25-	+35	1.95+2.93	4.88	1550	7.1	,í -	99 .:						
]	25-	+50	1.78+3.57	5.35	1600	7.3		99						
]	35-	⊦35	2.67+2.67	5.34	1600	7.3		99						
-	35-	+50	2.42+3.22	5.64	1625	7.5		99						
	50-	+50	2.91+2.91	5.82	1640	7.5	99							
1	25+2	5+25	1.78+1.78+1.78	5.34	1600	7.3		99						
MA56EV1	25+2	5+35	1.62+1.62+2.42	5,66	1625	7.5		99						
$\begin{array}{ c c c c c c c c c c c c c c c c c c c$														